

# QFX<sup>®</sup>

WHERE THE PARTY BEGINS<sup>™</sup>



## Car Rear View Camera User Manual

Thank you for purchasing the CAM-3. Installation of this rear view backup camera system should be performed by an automotive equipment installation specialist.

### Safety:

1. In order to maintain optimal operation, the camera should be cleaned regularly. Remove any dirt, water droplets, snow, etc. in order to ensure best image quality.
2. Although the camera is an IPX-rated device, it should not be washed with a jet of water under high pressure as it may damage the camera lens.
3. Keep the camera cables away from the vehicle's exhaust system, engine or heat-generating components.
4. The camera is designed to operate on 12V DC voltage. Do not use attempt to connect it to vehicles that supply 24V DC as it may permanently damage the unit.
5. Specification are subject to change without prior notice.

### Box Contents:




**Installation and Operation Guidelines:** (may vary depending on your specific vehicle)

Recommended tools that you may need to complete this installation include a flathead and Phillips screwdrivers, digital multi-meter, wire strippers/cutters, electrical tape, cable ties, double-stick tape and more depending on your vehicle.

- Make sure your vehicle is turned off and that the parking brake is engaged
- Safely disconnect the vehicle positive (+) and negative (-) battery terminals
- Remove the license plate (if necessary).
- Connect the power cable to the camera power input connector (red).
- Connect the power cable to the reverse light of the vehicle. NOTE: As an alternative, some aftermarket stereo wiring harnesses have a direct connection to reverse power (+12VDC).
- Connect the video cable to the camera video connector (yellow).
- Extend the video cable to the front of the vehicle and connect it to the video monitor or backup mirror display.
- After checking all connection, safely reconnect the battery terminals.
- Start the vehicle.
- Put the car in reverse and with brake engaged check if the monitor turns on and displays the rear video feed.
  - o If it works, turn the car off.
  - o If it doesn't work, recheck all connections and retry. Please note that in order for the display to show the video feed, it needs a signal to alert the system that the car is in reverse.
- Once proper operation and alignment has been confirmed, affix the camera (or license plate camera) to the vehicle's frame or license plate, protect and neatly organize wiring/cables using electrical tape, cable ties, double-stick tape, etc.

**Connections:**



**Specification:**

Image sensor	CCD
Signal System	NTSC/PAL
Effective Pixel	728 x 500
Sync System	Internal
Horizontal Resolution	500TVL

Min. Illumination	0.01lux/F1.2
Diagonal Angle	120°
Waterproof Rating	IP69K
Power Supply	12VDC
Working Temp.	-22F to 176°F (-30°C to 80°C)



## LIMITED PRODUCT WARRANTY POLICY

Before returning your Product for service under this Warranty, please (i) read the instruction manual carefully and visit our website at [www.qfxusa.com](http://www.qfxusa.com) for Product updates and extended support documentation (e.g., Common Troubleshooting Guides); (ii) if you are still having trouble with your Product, please contact the QFX Customer Support Department.

Subject to the terms and conditions herein, QFX, Inc. (herein after called "QFX") warrants to the original purchaser of the Product ("Customer") that for the applicable Warranty Period listed below, the Product will be free from defects in material or workmanship under normal, non-commercial use ("Defects").

Warranty Period encompasses, as listed below, separate "Coverage Periods" for Parts and Labor, each Coverage Period to begin from the original date of Customer purchase. If Customer returns a defective Product (or any component thereof) during the applicable Warranty Period, QFX will, at its option, during the specified Coverage Periods for Parts and Labor (as applicable either: (i) repair the Product (or, as applicable, any component thereof) or (ii) replace the Product (or, as applicable, any component thereof) with a new or refurbished Product (or, as applicable, any component thereof), in either case free of charge to Customer for Parts and/or Labor (as applicable) during the specified Coverage Period only, and excluding applicable shipping charges (noted below), for which the Customer is responsible. The foregoing states the Customer's exclusive remedy and QFX sole liability for breach of the limited warranty contained herein.

This warranty covers only normal use. This warranty is not transferable. QFX is not responsible for warranty replacement should the QFX label or logo be removed or should the product fail to be properly maintained or fail to function properly as a result of **misuse, abuse, immersion in liquids, improper installation, improper shipping, damage caused by disasters such as fire, flood, or service other than by QFX**. In addition, this warranty excludes any Product (or, as applicable, any component thereof) that has been subject to or Defects resulting from: (a) any neglect or misuse by a Customer, an accident, improper application, violation of operating instructions for the Product, any other Customer-induced damage, or the alteration or removal of any Product serial number; (b) any modification or repair to Product (or, as applicable, any component thereof) by any party other than QFX or a party authorized in writing by QFX; (c) any damage to Product (or, as applicable, any component thereof) due to power surges, incorrect electrical voltage, misconnection to any device, or malfunction of any device used with the Product (or, as applicable, any component thereof); (d) cosmetic damage to the Product (or, as applicable, any component thereof) caused by normal wear and tear; (e) shipping damage that occurs while the Product is in transit; (f) damage caused by heat sources, sunlight, electromagnetic conditions, or other climatic conditions or (g) any acts of God.

Product is sold to Customer for personal, non-commercial use only. Product is not warranted for Customer's commercial or rental use. In addition, Product is not warranted against failure, and should not be used by Customer for any application where (i) there is a risk that any data stored on Product will be breached or otherwise compromised, or (ii) the date stored on Product is relied upon for medical or lifesaving applications. QFX disclaims any Warranty for any of the foregoing uses to the fullest extent permitted by law. Customer assumes any and all risks associated with such uses of Product, and agrees to indemnify QFX for any damages claimed against QFX for such uses.

EXCEPT FOR EXPRESS WARRANTIES STATED ABOVE AND TO THE MAXIMUM EXTENT PERMITTED BY LAW, THE PRODUCTS ARE PROVIDED "AS IS" AND QFX DISCLAIMS ALL OTHER WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY (i) OF MERCHANTABILITY, (ii) OF FITNESS FOR A PARTICULAR PURPOSE, OR (iii) OF NON-INFRINGEMENT OF THIRD PARTY RIGHTS. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, IN NO EVENT WILL QFX BE LIABLE TO CUSTOMER OR ANY THIRD PARTY FOR ANY INDIRECT, SPECIAL, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY OR PUNITIVE DAMAGES, INCLUDING, WITHOUT LIMITATION, ANY LOST PROFITS OR REVENUES, LOSS OR INACCURACY OF ANY DATA OR COST OF SUBSTITUTE GOODS, REGARDLESS OF THE THEORY OF LIABILITY (INCLUDING NEGLIGENCE) AND EVEN IF QFX HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, QFX AGGREGATE LIABILITY TO CUSTOMER FOR ACTUAL DIRECT DAMAGES FOR ANY CAUSE WHATSOEVER SHALL BE LIMITED TO THE CUMULATIVE PRODUCT FEES PAID BY THAT CUSTOMER FOR THE PRODUCTS CAUSING THE DAMAGES, IF ANY.

This Warranty gives Customer specific rights, and Customer may also have other rights that vary from jurisdiction to jurisdiction. Warning: Some Products may contain components that are small enough to be swallowed. Please keep out of reach of children. In order for the return to be processed, you must send the Product PREPAID to the address below in the original packaging or reasonable substitute to prevent damage and include: (1) a dated sales receipt (which must have a purchase date that falls in the Warranty Period specified in the table below) that indicates the place of purchase, model number of Product, and amount paid, (2) a detailed description of Customer's problem with Product, (3) Customer's full name, phone number, and return address, (3) all of the accessories that came with the Product package must be sent along with the main Product, (4) a cashier's check or money order payable to QFX, Inc., in the amount specified for the item in the product table below for return shipping and handling. If in the case you cannot provide a money order or cashier's check, you can contact The QFX Customer Support Representative to arrange payment via credit card. No returned Product will be shipped back to a PO BOX. If a returned Product is found to have no problem and/or does not include ALL of the requirements indicated above, it may be returned back to the customer and will not be processed.

FOLLOW US @QFXUSA



**QFX USA®, Inc.**

RMA Processing  
Customer Support Department  
2957 E. 46th Street | Vernon, CA 90058

✉ support@qfxusa.com  
☎ (800) 864-CLUB (2582) or (323) 864-6900  
🌐 qfxusa.com  
🕒 Hours of Operation: Monday - Friday, 9am - 5pm PST

All prices and details below are for US Destinations excluding, Hawaii, Alaska and Puerto Rico. For excluded destinations and NON US destinations, please contact The QFX Customer Support Department directly for additional shipping fees and return instructions.

If you do not find your Product below, your Product model conflicts with multiple categories, and/or are unsure of which category the Product you have purchased will fall under, please contact our Customer Support Department for further instruction.

In order to determine the exact shipping cost that must be included with your product or paid for the product being returned, please refer to the table below. Please find the product you wish to return by category or model number prefix. QFX will not provide any return or refund to any customer for merchandise and will only honor the Limited Warranty restrictions mentioned in this document.

Please make sure to follow all directions prior to shipping back your item. If you are not sure what the shipping cost for your item is, or if your item category conflicts in the table below, please feel free to contact the QFX Support Department for further assistance.

PRODUCT CATEGORY	HANDLING	LABOR	PARTS
Earphones, Headphones, Pocket Radios, & Small Bluetooth vSpeakers	\$5.00	1 Year	1 Year
Personal Stereos	\$10.00	1 Year	1 Year
Portable Radio/Cassette	\$15.00	1 Year	1 Year
Large Portable Radio Cassette	\$20.00	1 Year	1 Year
Mobile Audio	\$10.00	1 Year	1 Year
Pro Audio SBX Systems	\$75.00	1 Year	1 Year
Pro Audio PBX Systems	\$75.00	1 Year	1 Year
Televisions	\$25.00	1 Year	1 Year
Telephones	\$10.00	1 Year	1 Year

THE WARRANTY AND REMEDY PROVIDED ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESSED OR IMPLIED WARRANTIES INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT OR FITNESS FOR A PARTICULAR PURPOSE. SOME LAWS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES. IF THESE LAWS APPLY, THEN ALL EXPRESSED OR IMPLIED WARRANTIES ARE LIMITED TO THE WARRANTY PERIOD IDENTIFIED ABOVE. UNLESS STATED HEREIN, ANY STATEMENT OR REPRESENTATIONS MADE BY ANY OTHER PERSONS OR FIRM ARE VOID. EXCEPT AS PROVIDED IN THIS WRITTEN WARRANTY, QFX SHALL NOT BE LIABLE FOR ANY LOSS, INCONVENIENCE, OR DAMAGE, INCLUDING DIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES, RESULTING FROM THE USE OR INABILITY TO USE THE QFX PRODUCT, WHETHER RESULTING FROM BREACH OF WARRANTY OR ANY OTHER LEGAL THEORY.

Some jurisdictions do not allow limitations on how long an implied warranty lasts, and some jurisdictions do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations and exclusions may not apply to you. This warranty gives you special legal rights and you may have other rights which vary from jurisdiction to jurisdiction.

Copyright Protected 2022 ©



[www.qfxusa.com](http://www.qfxusa.com)

# QFX<sup>®</sup>

WHERE THE PARTY BEGINS<sup>™</sup>



## Manual de usuario de la cámara de visión trasera del coche

Gracias por comprar la CAM-3. La instalación de este sistema de cámara retrovisora de visión trasera debe ser realizada por un especialista en instalación de equipos automotrices.

### La seguridad:

1. Para mantener un funcionamiento óptimo, la cámara debe limpiarse regularmente. Elimine la suciedad, las gotas de agua, la nieve, etc. para garantizar la mejor calidad de imagen.
2. Aunque la cámara es un dispositivo con clasificación IPX, no debe lavarse con un chorro de agua a alta presión, ya que podría dañar la lente de la cámara.
3. Mantenga los cables de la cámara alejados del sistema de escape del vehículo, el motor o los componentes que generan calor.
4. La cámara está diseñada para funcionar con un voltaje de 12 V CC. No intente conectarlo a vehículos que suministren 24 V CC, ya que puede dañar permanentemente la unidad.
5. Las especificaciones están sujetas a cambios sin previo aviso.

### Contenido de la caja:




**Directrices de instalación y funcionamiento:** (pueden variar según su vehículo específico)

Las herramientas recomendadas que puede necesitar para completar esta instalación incluyen destornilladores de cabeza plana y Phillips, multímetro digital, pelacables/cortadores, cinta aislante, bridas para cables, cinta adhesiva doble y más, según su vehículo.

- Asegúrese de que su vehículo esté apagado y que el freno de estacionamiento esté puesto
- Desconecte de forma segura los terminales positivo (+) y negativo (-) de la batería del vehículo
- Retire la matrícula (si es necesario).
- Conecte el cable de alimentación al conector de entrada de alimentación de la cámara (rojo).
- Conecte el cable de alimentación a la luz de marcha atrás del vehículo. NOTA: Como alternativa, algunos arneses de cableado estéreo del mercado de accesorios tienen una conexión directa a la potencia inversa (+12 VCC).
- Conecte el cable de video al conector de video de la cámara (amarillo).
- Extienda el cable de video al frente del vehículo y conéctelo al monitor de video o a la pantalla del espejo retrovisor.
- Después de comprobar todas las conexiones, vuelva a conectar de forma segura los terminales de la batería.
- Arrancar el vehículo.
- Ponga el automóvil en reversa y con el freno accionado verifique si el monitor se enciende y muestra la señal de video trasera.
  - o Si funciona, apague el coche.
  - o Si no funciona, vuelva a verificar todas las conexiones y vuelva a intentarlo. Tenga en cuenta que para que la pantalla muestre la transmisión de video, necesita una señal para alertar al sistema de que el automóvil está en reversa.
- Una vez que se haya confirmado el funcionamiento y la alineación correctos, fije la cámara (o la cámara de la placa de matrícula) al marco del vehículo o a la placa de matrícula, proteja y organice ordenadamente el cableado/los cables con cinta aisladora, bridas para cables, cinta adhesiva doble, etc.

**Conexiones:**



**Specification:**

Sensor de Imagen	CCD
Sistema de Señal	NTSC/PAL
Píxel Efectivo	728 x 500
Sistema de Sincronización	Internal
Resolucion Horizontal	500TVL

Mín. Iluminación	0.01lux/F1.2
Ángulo diagonal	120°
Clasificación impermeable	IP69K
Fuente de Alimentación	12VDC
Temperatura de Trabajo.	-22F to 176°F (-30°C to 80°C)

# QFX

WHERE THE PARTY BEGINS™



## Manuel d'utilisation de la caméra de recul de voiture

Merci d'avoir acheté le CAM-3. L'installation de ce système de caméra de recul doit être effectuée par un spécialiste de l'installation d'équipements automobiles.

### Sécurité:

1. Afin de maintenir un fonctionnement optimal, la caméra doit être nettoyée régulièrement. Enlevez toute saleté, gouttelettes d'eau, neige, etc. afin d'assurer la meilleure qualité d'image.
2. Bien que la caméra soit un appareil classé IPX, elle ne doit pas être lavée avec un jet d'eau à haute pression car cela pourrait endommager l'objectif de la caméra.
3. Éloignez les câbles de la caméra du système d'échappement du véhicule, du moteur ou des composants générant de la chaleur.
4. La caméra est conçue pour fonctionner sur une tension continue de 12 V. N'essayez pas de le connecter à des véhicules alimentés en 24 V CC car cela pourrait endommager l'appareil de manière permanente.
5. Les spécifications sont sujettes à modification sans préavis.

### Contenu de la boîte :




**Directives d'installation et de fonctionnement:** (peut varier en fonction de votre véhicule spécifique)

Les outils recommandés dont vous pourriez avoir besoin pour effectuer cette installation comprennent un tournevis à tête plate et cruciforme, un multimètre numérique, des pinces à dénuder/coupe-fil, du ruban électrique, des attaches de câble, du ruban adhésif double face et plus encore selon votre véhicule.

- Assurez-vous que votre véhicule est éteint et que le frein de stationnement est serré
- Débranchez en toute sécurité les bornes positive (+) et négative (-) de la batterie du véhicule
- Retirez la plaque d'immatriculation (si nécessaire).
- Connectez le câble d'alimentation au connecteur d'entrée d'alimentation de la caméra (rouge).
- Connectez le câble d'alimentation au feu de recul du véhicule. REMARQUE : Comme alternative, certains faisceaux de câbles stéréo du marché secondaire ont une connexion directe à l'alimentation inverse (+12 VDC).
- Connectez le câble vidéo au connecteur vidéo de la caméra (jaune).
- Étendez le câble vidéo à l'avant du véhicule et connectez-le au moniteur vidéo ou à l'affichage du rétroviseur de recul.
- Après avoir vérifié toutes les connexions, rebranchez en toute sécurité les bornes de la batterie.
- Démarrez le véhicule.
- Mettez la voiture en marche arrière et avec le frein serré, vérifiez si le moniteur s'allume et affiche le flux vidéo arrière.
  - o Si cela fonctionne, éteignez la voiture.
  - o Si cela ne fonctionne pas, revérifiez toutes les connexions et réessayez. Veuillez noter que pour que l'écran affiche le flux vidéo, il a besoin d'un signal pour alerter le système que la voiture est en marche arrière.
- Une fois le bon fonctionnement et l'alignement confirmés, fixez la caméra (ou la caméra de la plaque d'immatriculation) sur le châssis ou la plaque d'immatriculation du véhicule, protégez et organisez soigneusement le câblage/les câbles à l'aide de ruban électrique, d'attaches de câble, de ruban adhésif double face, etc.

**Connexions:**



**Specification:**

Capteur d'images	CCD
Système de Signalisation	NTSC/PAL
Pixel Effectif	728 x 500
Système de Synchronisation	Internal
Résolution Horizontale	500TVL

Min. Éclairage	0.01lux/F1.2
Angle diagonal	120°
Indice d'étanchéité	IP69K
Source de Courant	12VDC
Température de travail.	-22F to 176°F (-30°C to 80°C)